



ROTOBALE COMPACTION SOLUTIONS INC.

Rotobale RC Series Self Contained Compactors

Rotobale has used its' 40 years of manufacturing waste and recycling equipment to design our RC Series Self Contained Compactors with the most compaction in the industry; utilizing our low ram face design combined with 16" ram penetration more waste and recyclables get packed into the container, making it the most cost-efficient compactor **by reducing your trips to the landfill.**



Product Features:

- **16" RAM PENETRATION** within the container, the "most in the industry"
- **RAM DWELLS AGAINST THE LOAD** increasing compaction
- **SOLID STEEL BUBBLE DOOR** for more compaction capacity
- **NEWLY DESIGNED "NO LEAK"** door gasket
- **4.5" CROSS CYLINDER DESIGN** ideal for tight spaces allowing for a steeper chute
- **43" FEED HEIGHT** designed for easy accessibility
- **MANUFACTURER'S SAFETY DECLARATION**

Benefits:

- **Reduces haulage costs** as the RC Series of Self Contained Compactors pack more than the industry standard
- **Eliminates liquid/waste spillage, leakage and odour** utilizing our liquid tight seal
- **Provides a safer and cleaner environment as there is NO ACCESS** to the container
- **Increase waste and recycling capacity up to 35%** with our 44 yard self contained compactor

Ideal For: Supermarkets, Restaurants, Plaza's, Hotel's and Manufacturing Plants

Canada's leading manufacturer of waste compaction and recycling equipment



Rotobale Compaction Solutions Inc. :-: 7232 Arthur Road #5 West :-: Kenilworth, ON N0G 2E0
T: (519) 323.3673 :-: TF: (800) 565.8027 :-: F: (519) 323.3816 :-: www.rotobalecompaction.ca



ROTOBALE COMPACTION SOLUTIONS INC.

7232 Arthur Road #5 West
Kenilworth, ON N0G 2E0

T: (519) 323.3673

TF: (800) 565.8027

F: (519) 323.3816

www.rotobalecompaction.ca



MODEL "RC" SELF CONTAINED COMPACTOR GENERAL SPECIFICATIONS

	20 CU YD	30 CU YD	35 CU YD	40 CU YD	44 CU YD
Dimensions					
Overall Length	A 204"	250"	274"	300"	324"
Overall Height	B 100"	100"	100"	100"	100"
Overall Width (container rear)	C 102"	102"	102"	102"	102"
Overall Width (container front)	D 88"	88"	88"	88"	88"
Chargebox WxLxD	ExFxG 60"x43"x28"	60"x43"x28"	60"x43"x28"	60"x43"x28"	60"x43"x28"
Feed Height	H 43"	43"	43"	43"	43"
Performance Characteristics					
Operational Compaction Force	63,600 lbs	63,600 lbs	63,600 lbs	63,600 lbs	63,600 lbs
Maximum Compaction Force	76,320 lbs	76,320 lbs	76,320 lbs	76,320 lbs	76,320 lbs
Ram Penetration (within container)	16"	16"	16"	16"	16"
Electrical / Hydraulic Specifications					
Electrical Motor	10 / 5 HP	10 / 5 HP	10 / 5 HP	10 / 5 HP	10 / 5 HP
Pump Capacity	10.8 / 5.4 gpm	10.8 / 5.4 gpm	10.8 / 5.4 gpm	10.8 / 5.4 gpm	10.8 / 5.4 gpm
Cycle Time	45s / 90s	45s / 90s	45s / 90s	45s / 90s	45s / 90s
Voltage	To suit customers needs				
Electrical Control Voltage	110VAC	110VAC	110VAC	110VAC	110VAC
Normal Pressure	2000 psi	2000 psi	2000 psi	2000 psi	2000 psi
Maximum Pressure	2400 psi	2400 psi	2400 psi	2400 psi	2400 psi
Hydraulic Cylinder	(2) 4.5"	(2) 4.5"	(2) 4.5"	(2) 4.5"	(2) 4.5"

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE TO ACCOMMODATE EQUIPMENT IMPROVEMENTS



ROTOBALE COMPACTION SOLUTIONS INC.

Rotobale RC Series Self Contained Compactors

**Proud Canadian
Manufacturer
Since 1968**

