

ROTOBALE COMPACTION SOLUTIONS INC.

The Rotobale line of vertical compactors has been specifically designed to contain wet or dry waste materials. They eliminate the use of unsightly open refuse containers and minimizes the possibility of pilferage and unauthorized use.

The RV-Series of vertical compactors are ideal for situations where space may be restricted, the volume of wet waste does not justify a larger system, or a roll-off collection service is not available.

These vertical units are versatile and easy to operate. Their compact design make them ideal for shopping plazas, restaurants, hotels/motels, fast food locations, hospitals, nursing homes, schools, and many more locations. They can either be used on the exterior or the interior of the building.

The vertical compactors are available in 4, 6, and 8 yard capacities. All models are equipped with the Roto-teck control cycle system, allowing for improved compaction and higher load density. This results in less trips for your hauler which translates into savings for you.

Product Features:

- No spillage
- Low maintenance
- Space saving layout
- Ultra-safe operation
- Auto-cycle compacting
- Lockable control panel

Vertical Compactor RV-4 / RV-6 / RV-8



Canada's leading manufacturer of waste compaction and recycling equipment











ROTOBALE COMPACTION SOLUTIONS INC.

7232 Arthur Road #5 West Kenilworth, ON NOG 2E0

T: (519) 323.3673

TF: (800) 565.8027 F: (519) 323.3816

www.rotobalecompaction.ca

MODEL "RV" VERTICAL COMPACTOR GENERAL SPECIFICATIONS

		4 CU YD	6 CU YD	8 CU YD
Dimensions				
Overall Length	Α	88"	88"	88"
Overall Width	В	93"	93"	93"
Overall Height	С	74.5"	94.5"	102"
Feed Height	D	42.5"	58.5"	65.5"
Charge Opening HxW	ExF	28" x 48"	28" x 48"	28" x 48"
Weight (lbs.)		3500	3600	3700
Performance Characteristics				
Operational Compaction Force		22,400 lbs	22,400 lbs	22,400 lbs
Maximum Compaction Force		24,900 lbs	24,900 lbs	24,900 lbs
Ram Penetration		15"	15"	15"
Electrical / Hydraulic Specification	ns			
Electrical Motor		2 HP	2 HP	2 HP
Pump Capacity		2.0 gpm	2.0 gpm	2.0 gpm
Cycle Time		14s	14s	14s
Voltage		To suit customers needs		
Electrical Control Voltage		110 VAC	110 VAC	110 VAC
Normal Pressure		1800 psi	1800 psi	1800 psi
Maximum Pressure		2000 psi	2000 psi	2000 psi
Hydraulic Cylinder		(1) 4"	(1) 4"	(1) 4"

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE TO ACCOMMODATE EQUIPMENT IMPROVEMENTS



ROTOBALE COMPACTION SOLUTIONS INC.

Vertical Compactor

Manufacturer









